SONY

# XM-1252GTR
Amplifiers

## Key Features

- 800W Max Power
- 125Wx2 RMS into 4 ohms
- 340Wx1 RMS into 4 ohms
- High Level Sensing Power On
- 800W Max Power
- 125Wx2 RMS into 4 ohms
- 340Wx1 RMS into 4 ohms
- High Level Sensing Power On
- Variable 50 - 300 Hz low pass filter
- 40 Hz EQ boost
- MOSFET power supply
- RCA & speaker level inputs
- Line level thru-put
- CEA-2006 Power Compliant

## Specifications

### Audio

Frequency Response: 5-50 Hz
Input Level: .3-6V (Line level input)
Operation: Voltage (V)- 10.5-16
Noise Level: 100 dB

### Power

Power Consumption (in Operation): 800 Watts
Current Drain: 32A
Power Consumption: Bridged into 4 ohms, THD% 340, .15

### Dimensions

Weight: 9 lbs, 12 oz (4.4 Kg)
Measurements: 10 7/8 x 2 1/4 x 12 3/4" (276 x 57 x 324mm)

UPC Code: 027242686724

like.no.other™

SONY

# XM-1252GTR

## Amplifiers

Please visit the Dealer Network for more information at www.sony.com/dn

©2006 Sony Electronics Inc.
Reproduction in whole or in part without written permission is prohibited.
Sony is a trademark of Sony. All other trademarks are property of their respective owners.
Features and specifications are subject to change without notice. Non-metric weights and measures are approximate.